MESHES PER		WIRE	WIDTH	OPEN	LBS. PER	
LINEAL INCH		DIAMETER	OPENING	AREA	100 SQ. FT. S.S	
<u>1"</u>						
	C to C	.120"	.880"	77.40%	93	
	(W)	.080"	.920"	84.60%	42	
	(W)	.063"	.937"	87.80%	26	
3/4"						
	C to C	.105"	.645"	73.90%	95	
	(W)	.080"	.670"	79.80%	55	
	(H)	.063"	.687"	83.90%	34	
2		.135"	.365"	53.30%	242	
		.120"	.380"	57.80%	190	
		.105"	.395"	62.40%	144	
		.080"	.420"	70.60%	83	
	(W)	<u>.063"</u>	.437"	76.40%	51	
		.047"	.453"	82.10%	28	
	(W)	.041"	.459"	84.30%	22	
<u>2</u> 1/2		.063"	.337"	71%	64	
3		.120"	.213"	40.80%	294	
		.092"	.241"	52.30%	169	
		.080"	.253"	57.60%	126	
		.063"	.270"	65.60%	78	
		<u>.054"</u>	.279"	70.10%	57	
		.047"	.286"	73.60%	43	
		.041"	.292"	76.70%	33	
	(H)	032"	.301"	81.50%	20	
4		.120"	.130"	270%	389	
		.105"	.145"	33.60%	306	
		.080"	.170"	46.20%	172	
		.063"	.187"	56.00%	105	
		<u>.047"</u>	.203"	65.90%	58	
		.035"	.215"	74.00%	32	
	(W)	.032"	.218"	76.00%	26	
		.028"	.222"	78.90%	20	
	(H)	.025"	.225"	81.00%	16	
		.020"	.230"	84.60%	11	
5		.105"	.095"	22.60%	379	
		.047"	.153"	58.50%	73	
		<u>.041"</u>	.159"	63.20%	55	
		.035"	.165"	68.10%	40	
	4.5	.023"	.177"	78.30%	17	
	(H)	.020"	.180"	81.00%	13	

6		.080"	.087"	27.20%	259
<u>~</u>		.063"	.104"	38.90%	163
		.054"	.113"	46.00%	118
		.047"	.120"	51.80%	88
		.035"	.132"	62.70%	48
		.028"	.139"	69.60%	31
	(H)	.020"	.147"	77.80%	16
	(11)	.020	.147	77.0070	10
7		.028"	.115"	64.80%	36
		.020	.113	04.00 /6	30
0		0021	0001	24 600/	246
<u>8</u>		.063"	.062"	24.60%	216
		.047"	.078"	38.90%	121
		.041"	.084"	45.20%	91
		.035"	.090"	51.80%	65
		.032"	.093"	55.40%	54
		<u>.028"</u>	.097"	60.20%	41
		.025"	.100"	64.00%	33
		.023"	.102"	66.60%	28
		.020"	.105"	70.60%	21
	(H)	.017"	.108"	74.60%	15
		.011"	.114"	83.20%	4
<u>10</u>		.047"	.053"	28.10%	148
		.035"	.065"	42.30%	83
		.032"	.068"	46.20%	69
		.028"	.072"	51.80%	52
		<u>.025"</u>	.075"	56.30%	41
		.023"	.077"	59.30%	35
		.018"	.082"	67.20%	21
		.016"	.084"	70.60%	17
	(H)	.015"	.085"	72.30%	15
<u>12</u>		.041"	.042"	25.40%	137
		.035"	.048"	33.20%	102
		.028"	.055"	43.60%	64
		<u>.023"</u>	.060"	51.80%	42
		.018"	.065"	60.80%	26
		.017"	.066"	62.70%	23
		.015"	.068"	66.60%	18
		.011"	.072"	74.60%	10
<u>14</u>		.032"	.039"	29.80%	101
		.028"	.043"	36.20%	76
		<u>.020"</u>	.051"	51.00%	37
		.018"	.0534"	55.10%	29.9
		.014"	.057"	63.70%	18
		.011"	.060"	70.60%	11
	(B)	.009"	.062"	76.40%	7

10		005"	007511	40.400/	407	
<u>16</u>		.035"	.0275"	19.40%	137	
		.028"	.0345"	30.50%	84	
		.025"	.0375"	36.00%	69	
		.023"	.0395"	39.90%	58	
		.020"	.0423"	46.20%	43	
		<u>.018"</u>	.0445"	50.70%	35	
		.016"	.0465"	55.40%	27	
		.011"	.052"	67.90%	13	
	(B)	.009"	.0535"	73.30%	9	
		.0065"	.056"	80.30%	5	
<u>18</u>		.032"	.0236"	18.00%	129	
		<u>.017"</u>	.0386"	48.30%	35	
	(B)	.009"	.0466"	70.20%	10	
20		.025"	.0250"	25.00%	85	
		.023"	.0270"	29.20%	71	
		.020"	.0300"	36.00%	55	
		.018"	.0320"	41.00%	44	
		<u>.016"</u>	.0340"	46.20%	34	
		.015"	.0350"	49.00%	30	
		.014"	.0360"	51.80%	26	
		.013"	.0370"	54.80%	22	
		.010"	.0400"	64.00%	13	
	(B)	.009"	.0410"	67.20%	11	
22	(B)	.0075"	.0380"	69.70%	8	
24		.023"	.0187"	20.10%	88	
		.016"	.0257"	38.00%	42	
		<u>.014"</u>	.0277"	44.20%	32	
		.0135"	.0282"	45.80%	29	
		.010"	.0317"	57.90%	16	
		.009"	.0330"	61.60%	13	
	(B)	.0075"	.0342"	67.20%	9	
<u>26</u>						
		.018"	.0205"	28.40%	57	
		.017"	.0215"	31.20%	53	
	(B)	.0075"	.0310"	64.80%	10	
28		.018"	.0177"	24.60%	62	
_ 	(B)	.0075"	.0282"	62.40%	10	
	. ,					

<u>30</u>		.016"	.0173"	26.90%	52
		.015"	.0183"	30.10%	47
		.014"	.0193"	33.50%	41
		.013"	.0203"	37.10%	35
		<u>.012"</u>	.0213"	40.80%	29
		.011"	.0223"	44.80%	25
		.010"	.0233"	48.90%	20
		.0095"	.0238"	51.00%	18
		.009"	.0243"	53.10%	16
	(B)	.0065"	.0268"	64.80%	8
	. ,				
34	(B)	.0065"	.0229"	60.70%	10
	(6)	.0003	.0229	00.7070	10
25		040"	04.0011	22.000/	25
<u>35</u>		.012"	.0166"	33.80%	35
		.010"	.0186"	42.40%	24
<u>36</u>	(B)	.0065"	.0213"	58.70%	10
<u>40</u>		.0135"	.0115"	21.20%	53
		.013"	.0120"	23.00%	49
		<u>.010"</u>	.0150"	36.00%	28
		.0095"	.0155"	38.40%	25
		.009"	.0160"	41.00%	22
		.0085"	.0165"	43.60%	20
	(B)	.0065"	.0185"	54.80%	11
	(-/	10000	10.100	0 1100 / 0	
43	(B)	.005"	.0183"	61.60%	9
	(5)	.003	.0100	01.0070	
45		0075"	04.47"	42.000/	47
<u>45</u>		.0075"	.0147"	43.80%	17
<u>46</u>	(B)	.0055"	.0162"	55.80%	9
48	(B)	.0045"	.0163"	61.50%	10
<u>50</u>		.011"	.0090"	20.30%	42
		<u>.009"</u>	.0110"	30.30%	28
		.0085"	.0115"	33.10%	25
		.008"	.0120"	36.00%	22
		.0075"	.0125"	39.10%	19
		.0055"	.0145"	52.60%	11
	(B)	.0045"	.0155"	60.10%	10
	ν=/			1,113,0	
54	(B)	.004"	.0145"	61.50%	11
	(6)	.004	.0145	01.30/0	
F.0	(D)	004"	0400"	00.000/	44
<u>56</u>	(B)	.004"	.0138"	60.20%	11
<u>58</u>	(B)	.004"	.0132"	59.00%	8

<u>60</u>	(TW)	.011"	.0057"	11.70%	53
		.009"	.0077"	21.30%	34
		<u>.0075"</u>	.0092"	30.50%	24
		.007"	.0097"	33.90%	20
		.0065"	.0102"	37.50%	17
		.006"	.0107"	41.20%	15
	(B)	.0045"	.0122"	53.30%	8
	(B)	.004"	.0127"	57.80%	8
	, ,				
80	(TW)	.007"	.0055"	19.40%	27
	(111)	.007 .0055"	.0070"	31.40%	17
	(D)				
	(B)	.0037"	.0088"	49.60%	7
<u>84</u>	(B)	.0035"	.0084"	49.80%	7
<u>88</u>	(B)	.0035"	.0079"	47.90%	7
90	(B)	.0035"	.0076"	46.80%	7
94	(B)	.0035"	.0071"	45.00%	8
	()				_
100		.0045"	.0055"	30.30%	16
<u> 100</u>		.0043 .004"	.0060"	36.00%	11
		.0035"	.0065"	42.30%	8
<u>105</u>	(B)	.003"	.0065"	46.90%	6
<u>120</u>	(TW)	.004"	.0043"	26.80%	15
		<u>.0037"</u>	.0046"	30.90%	13
	(B)	.0026"	.0058"	47.30%	5
135	(B)	.0023"	.0051"	47.40%	5
<u>145</u>	(B)	.0022"	.0047"	46.40%	5
	(-/			131.070	,
150		.0026"	.0041"	37.40%	7
130		.0020	.0041	37.40%	,
465		0005"	0005"	00.400	
<u>160</u>		.0025"	.0038"	36.40%	8
<u>165</u>	(B)	.0019"	.0042"	47.10%	4
<u> 180</u>		.0023"	.0033"	34.70%	8
200	(TW)	.0023"	.0026"	29.10%	7.2
	` ′	.0021"	.0029"	33.60%	6.3
	(B)	.0016"	.0034"	46.20%	3.4
	(-,	.50.0	.500 7	. 3.23 /0	5. .
222	(D)	004.4"	0000"	46.000/	2
230	(B)	.0014"	.0029"	46.00%	3

250	(TW)	<u>.0016"</u>	.0024"	36.00%	4.3
	(B)	.0014"	.0025"	42.00%	4.1
<u>270</u>	(TW)	<u>.0016"</u>	.0021"	32.20%	5.3
	(B)	.0014"	.0022"	38.00%	5.1
<u>325</u>	(TW)	<u>.0014"</u>	.0017"	30.00%	4.4
	(B)	.0011"	.0020"	42.00%	4.1
<u>400</u>	(TW)	<u>.0011"</u>	.0015"	36.00%	3.3
500	(TW)	<u>.0010"</u>	.0010"	25.00%	3.5
<u>635</u>	(TW)	.0008"	.0008"	25.00%	3